




## SPRAY

Product	Type of Lubricant	Operating temperature range (°C)	Characteristics and Fields of Application
<b>3560</b>	SYNTHETIC OIL	-10 +150	Synthetic oil with high adhesiveness. Anti-drop, penetrating for chains operating in critical conditions.
<b>APS</b>	SYNTHETIC OIL	Not significant	Synthetic anti-glitter oil for continuous welding. Anti-glitter during welding process to avoid the breakage of wire welding.
<b>AT</b>	MINERAL GREASE	-15 +240	Infusible grease containing molybdenum disulphide powder. Suitable for bearings and oven chains working at high temperature.
<b>COPPER</b>	PASTE	-15 +1000	Special infusible compound containing an high percentage of copper powder. Suitable for bolts, screw operating at very high temperature subjected to static loads.
<b>DLF</b>	VARNISH	-180 +450	Dry lubricants containing molybdenum disulphide powder. Suitable for gears pretreatment, stenter adjustments, generally where is required a dry lubrication.
<b>DS 20</b>	VARNISH	-40 +280	Dry lubricant containing PTFE powder, nonstick moulds. Generally suggested where is required a dry lubrication to improve the sliding and reduce the friction.
<b>ELETTROLOC</b>	MINERAL OIL	Not significant	Electrical contact lubricant and cleaner. Till 240 Volt.
<b>I.SCO</b>	MINERAL OIL	-20 +100	Highly viscous and adhesive lubricant, suitable for open gear and wire ropes lubrication.
<b>MF</b>	SEMI-SYNTHETIC OIL	-20 +250 (oily layer) -20 +450 (oily dry)	Semi-synthetic oil containing molybdenum disulphide. Suggested for bearings, chains, conveyor into ovens and tunnels.
<b>MV 40 LUBRICANT</b>	WATER REPELLENT LUBRICANT	Not significant	Multipurpose product composed by a mixture of non-flammable fluids. Thanks to their action it solves many problems related to lubrication and machinery maintenance. Anti-rust protection, releasing agent with rapid effect.
<b>MOLY F</b>	MINERAL OIL	-12 +250 (oily layer) -20 +450 (oily dry)	Special oil with high molybdenum disulphide concentration for textile machinery.
<b>MOLY CHAIN AL</b>	PAO 	-30 +250	Non-toxic synthetic oil for high loads and temperature. Suitable for rolling bearings chains, conveyor working in food industry. Product code registered with <b>NSF H1 group No.148585</b> .

Product	Type of Lubricant	Operating temperature range (°C)	Characteristics and Fields of Application
MOLYGRAF GS	GRAPHITE	-50 +690	Free lubricant base oil with graphite micronized for extreme application. Made a lubricant film that cover the surface and polymerizes in 12 hours.
MOLYSIL	SILICON OIL	-30 +150	Silicon oil. Suitable as releasing agent for moulds, insulating for electric cables.
MULTIGREASE	MINERAL GREASE	-20 +150	Multipurpose grease with medium life for all type of equipments.
MULTISBLOC	MIXTURE OF SOLVENTS	Not significant	Releasing agent for ferrous and not ferrous coupling. Suitable for bearings, bolts, nuts, pins stuck from rust.
MULTISBLOC FG 	MIXTURE OF SOLVENTS	-20 +140	Non-toxic fluid with penetrating, protective and lubricant properties. Multipurpose used in different application into food, cosmetic and pharmaceutical industry. Product code registered with <b>NSF H1 group No. 148156.</b>
PASTA 35	MINERAL PASTE	-40 +400	Anti-seize paste containing molybdenum disulphide. Used as anti-seize for machine tools guides, bolts, gears, into navy, aeronautic and automotive industry.
POLVERE NU	POWDER MoS2	-100 +450	Molybdenum disulphide powder according patented methods (1 micron). Suitable for dry drawing, high precision mechanisms, optical tools and oxygen valves.
RAPID CLEAN	PETROLEUM SOLVENT	Not significant	Solvent with high detergent power. Degreasing and cleaning of mechanical parts.
SDS	SILICON FLUID MODIFIED	-30 +150	Antistatic synthetic oil. Mould release agent for rubber and plastic industry. It doesn't need to degrease the treated parts.
SAFETYCUT 3	MINERAL OIL	Not significant	Cooling lubricant for metal, even stainless steel for drilling, thread and tapping.
SED LUBE	SYNTHETIC OIL	-10 +150	Synthetic oil, high adhesive power, for chains. Anti-drop, suitable for all type of chains working at high speed.
SPECIAL TF	SYNTHETIC OIL AND SOLVENT	-25 +250	Synthetic oil containing micronized PTFE with special solvent. Suitable as lubricant detergent, releasing agent and also able to protect the surface. This product is waiting for the <b>NSF register code H1 group.</b>
MOLY TEF 	GREASE MINERAL ATOXIC	-30 +170	Grease containing PTFE and anti-oxidants additives. Suitable for bolts, joints, kinematic, working in a wide range of temperatures. Product code registered with <b>NSF H1 group No. 148157.</b>
TEX LUBE	MINERAL OIL	Not significant	Special lubricant containing EP, anti-wear, anti-oxidant and anti-static additives. Suitable for turnbuckles, fishermen, splicer, scissors used in the textile industry.
WFK	MINERAL OIL ANTI-CORROSION	Not significant	Rust inhibitor with oil film. Suitable for medium term protection and indoor storage components.